

Snel tabel telekranen en torenkranen



Afst (m)	45 T AT	50 T AT	70 T AT	85 T AT	100 T AT	120 T AT	140 T AT	365 AT3 SN	477 AT4 SN	498 AT4 SN	598 AT5 SN	599 AT5 SN	37 Tm ALK	45TM ALK	66TM ALK	Afst (m)
3	45.00	50.00	70.0	85.0	100.0	120.0	140.0	5.00	7.00	8.00	8.00	9.00	7.00	13.50	16.00	3
4	28.00	38.10	51.2	73.7	73.7	73.7	100.5	5.00	7.00	8.00	8.00	9.00	7.00	9.50	13.00	4
6	24.00	26.40	34.5	52.3	56.2	56.6	77.6	5.00	7.00	8.00	8.00	9.00	5.80	6.70	9.30	6
8	13.80	16.00	25.2	33.9	42.1	44.8	58.2	5.00	7.00	8.00	8.00	9.00	4.10	4.50	6.90	8
10	10.90	12.40	18.7	23.6	30.7	34.7	43.6	5.00	7.00	8.00	8.00	9.00	3.00	3.60	5.40	10
12	8.60	9.50	14.7	18.1	23.5	26.2	33.0	5.00	6.60	8.00	8.00	9.00	2.35	3.00	4.40	12
14	6.80	7.60	11.4	14.3	18.8	21.2	26.8	4.20	5.50	7.20	7.20	8.30	1.95	2.50	3.65	14
16	5.50	6.10	9.2	11.5	15.4	17.6	22.1	3.60	4.70	6.15	6.15	7.15	1.65	2.25	3.10	16
18	4.50	5.10	7.6	9.5	13.3	14.8	18.8	3.15	4.10	5.35	5.35	6.20	1.40	1.70	2.00	18
20	3.70	4.30	5.8	8.0	11.3	12.6	16.1	2.75	3.60	4.75	4.75	5.50	0.90	1.00	1.50	20
22	3.10	3.70	5.3	6.7	9.9	11.3	14.0	2.50	3.25	4.25	4.25	4.95	0.50	0.80	1.30	22
24	2.60	3.10	4.5	5.7	8.7	9.9	12.1	2.25	2.90	3.85	3.85	4.50		0.70	1.10	24
26	2.20	2.60	3.7	4.9	7.7	8.8	10.9	2.10	2.65	3.50	3.50	4.10		0.60	1.00	26
28	1.80	2.20	3.3	4.2	6.8	7.9	9.7	1.90	2.45	3.25	3.25	3.75		0.35	0.80	28
30	1.40	1.50	3.0	3.6	6.1	7.1	8.7	1.70	2.25	3.00	3.00	3.45			0.60	30
32	1.00	1.20	2.2	3.0	5.4	6.4	7.4		2.10	2.75	2.75	3.20			0.50	32
34	0.80	0.70	1.8	2.5	4.8	5.9	6.9		1.95	2.60	2.60	3.00				34
36	0.60	1.20	1.4	2.1	4.3	5.2	5.9		1.80	2.40	2.40	2.80				36
38		1.00	1.2	1.5	3.5	4.5	5.3		1.70	2.25	2.25	2.65				38
40		0.80	1.1	2.2	2.7	4.0	4.7			2.15	2.15	2.50				40
42			0.9	1.8	2.3	3.2	4.2			2.00	2.00	2.40				42
44			0.8	1.4	2.0	2.9	3.6			1.90	1.90	2.20				44
46			0.7	1.1	1.7	2.6	3.2				1.80	2.10				46
48			0.6	0.9	2.1	2.5	2.9				1.70	2.00				48
50			0.4	0.6	2.0	2.2	2.8					1.90				50
52					1.8	2.2	2.5									52
56					1.1	1.7	1.9									56
60						0.8	1.2									60
62						0.7	1.0									62
GKL	32.00	40.00	40.50	46.00	50.50	50.50	60.00	30.40	38.00	44.00	48.00	50.00	20.50	17.00	16.75	
JBL	9.00	17.50	16.00	17.00	17.00	17.00	17.00							12.00	15.10	
SB	6.40	6.40	7.00	7.00	7.00	7.00	7.00	5.80	6.15	6.85	7.20	7.60	5.80	7.00	8.35	
SL	6.85	6.85	7.10	7.21	7.21	7.21	7.21	6.90	6.55	6.92	7.20	7.50	4.50	4.80	4.80	
DC	6.90	6.90	7.90	8.20	8.20	8.20	8.20	6.50	6.70	7.10	7.40	8.00	n.v.t.	n.v.t.	n.v.t.	
LW	9.00	9.00	11.00	11.17	11.17	11.17	11.17	9.25	10.80	11.28	12.20	12.60	7.50	7.80	7.80	

GKL = Hoofdgiek lengte
JBL = Hulp giek lengte

SL = Stempellengte
SB = Stempel breedte
DC = Draaicirkel ballast
LW = Onderwagen lengte

AT = All-terreinkraan
SN = Mobiele torenkraan

AK = Autokraan
ALK = Autolaadkraan